


LEAF FLOOR LAMP - US VERSION

BROBERG & RIDDERSTRÅLE ON THE DESIGN "Combining a light and elegant design with an energy-efficient LED technology, the Leaf Floor Lamp has a clean and refined expression. The asymmetric geometry of the design gives it an organic and friendly appearance, inspired by the leaves on a tree. Turn the leaf according to your needs and discover how the lamp will subtly transform its shape, adding a graphic and gentle light silhouette to any space."



Black













DESIGNED BY / YEAR OF DESIGN

Broberg δ Ridderstråle / 2012

ABOUT THE DESIGNER

Broberg & Ridderstråle are Swedish design and architectural partners. Their work combines an aesthetic rationality with a touch of humour and wit. Mats Broberg and Johan Ridderstråle have both graduated from Konstfack University of design with honours and have been awarded the Swedish Art Council's working grant. Their work has successfully been exhibited in Tokyo, Milan and London.

CATEGORY

Floor lamp

ENVIRONMENT

Indoor

DESCRIPTION

Leaf is a lamp series with an iconic silhouette in two sizes and a wide range of colours. Leaf uses energy-efficient LED technology and is equally suited for your private home as an office or commercial interior. The lamp's dim function makes it possible to control the light and mood in a room.

PRODUCTION PROCESS

Leaf is a result of a process combining turned and casted aluminum and steel, with a strong powder coating as paint.

MATERIAL

Aluminum, steel, brass, colored PVC cord

CORD LENGTH

180 cm / 71"

BULB INCLUDED

Yes

DIMMABLE FUNCTION

Yes

CLEANING AND CARE

Wipe off dust with dry cloth. If necessary use moist cloth, then dry off. Do not use abrasive cleaning agents.



LEAF FLOOR LAMP - US VERSION

GENERAL STANDARDS & CERTIFICATES

Conforms to UL STD. 153 Certified to CSA STD. C22.2 NO.25O.4



LAMP RATING

Voltage 120V Frequency 60Hz IP Rating 1P20

Socket 52 x non-replaceable LEDs

BULB SPECIFICATION

Item 52 x integrated, non-replacable LED

Watt8WLumen370 lmColor temperature3.000

Color consistency 3 McAdam steps

Lumen

 maintenance (70%)
 54.000 h

 CRI
 >90

 Dimmable
 yes

 Risk group
 Except